

Thickness Tolerances for Sponge Rubber Sheet

SPONGE RUBBER CLOSED CELL

THICKNESS	TOLERANCE +/-
1/16" (.062)	.015"
3/32" (.094)	.020"
1/8" (.125)	.020"
3/16" (.187)	.025"
1/4" (.250)	.025"
5/16" (.312)	.025"
3/8" (.375)	.035"
7/16" (.437)	.040"
1/2" (.500)	.040"
5/8" (.625)	.050"
3/4" (.750)	.065"
7/8" (.875)	.075"
1" (1.000)	.082"

SPONGE RUBBER OPEN CELL

THICKNESS	TOLERANCE +/-
1/16" (.062)	.010"
3/32" (.094)	.010"
1/8" (.125)	.012"
3/16" (.187)	.015"
1/4" (.250)	.025"
5/16" (.312)	.030"
3/8" (.375)	.030"
1/2" (.500)	.030"
3/4" (.750)	.045"
1" (1.000)	.045"

Thickness Tolerances for Solid Rubber Sheet

THICKNESS	TOLERANCE +/-	
0.031	& thinner	0.01
0.032	0.061	0.012
0.062	0.124	0.016
0.125	0.186	0.02
0.187	0.374	0.031
0.375	0.500	0.047
0.501	0.750	0.094
0.751	& thicker	10%